

## Overview

The CHEP Intercontinental Pallets seamlessly integrate into Australian destination racking and materials handling systems, these pallets eliminate the handling costs associated with manually loading shipping containers. Such improved container loading time enables better operational flow through and distribution centre utilisation.

Both lightweight and durable in design, Intercontinental Pallets are not only easy to handle, but also comfortably withstand the pressures of international supply chains.



## Features and Benefits

Nestable 4:1 ratio – reduces reverse logistics, carbon footprint and reduces pallet storage space

Flat surface – 3 cavities create feet and ability to efficiently 'nest'

Etched top deck – surface provides high friction and reduces product slippage

Rackable – pallet locks against front or rear face on both beams of standard Australian racking

No bottom boards – allows for easy entry of manual pallet jacks and eliminates the risk of boards falling

Beam location and forklift tyre entry indicators – assist mechanical handling equipment operators accurately lift and rack pallet, reducing impact and stock damage

Lightweight with high loading performance and 2-way entry – reduces manual handling risks and transport cost

Plastic platform – hygienic and no treatment required for export

1100 mm x 1100 mm footprint – efficiently fills all container types down to the narrower reefers and can drive efficient container unloading times; improving dock availability

## Specifications

### Dimensions - in millimeters

	Length	Width	Height
External	1100	1100	137

### Nominal Capacity and Weight

Tare Weight	10 kgs
-------------	--------

### Configuration and Stacking

Beam racking maximum payload 1,200 kg  
 Dynamic maximum payload 2,000 kg  
 Static load 4,000 kg  
 Should be used in operating temperatures between -20 and 40 degrees Celsius  
 Caution: This platform is not designed to function in drive through racking, so should never be stored in this configuration. Additional care is required when handling this platform in below 0 degrees Celsius environments to prevent unnecessary damage

## Notes

### Materials

Polypropylene composite with 30% long glass fibres

### Disclaimer

Specifications are subject to variation and may be changed without notice. The platform shown here represents the latest version. For some platforms, earlier versions are sometimes supplied when the latest are not available.