

Overview

A Dry Smooth Wall Intermediate Bulk Container (IBC). The CHEP Pallecon Solutions 1200 x 800 mm Dricon container is a foldable Intermediate Bulk Container providing strength for the safe handling of heterogeneous and fragile merchandise during warehousing, transportation and delivery.

Smooth inner & outer walls make this container ideal for hygienic environments and suitable for Food Grade products. Half-fold gates allow for easy access to contents. Available with an optional shelf to help protect more fragile products, and an optional lid to provide security and further product protection.



Features and Benefits

The reusable heavy duty folding plastic container helps reduce product damage, is fast and to easy to assemble and reduces storage requirements due to high load capacity in static storage

The smooth walls improve hygiene standards, are easy to clean and are impervious to moisture

The 3:1 fold down ratio saves costs on the space required for transport and storage

The optional shelf supports product in the top half of the container, while protecting product in the bottom half, while the optional lid protects products in storage/transit

Adjacent fold-down side doors make it easy access to product, and improves load and unload time

Optimised wall height enables full vehicle cube utilisation to optimise transport costs for product shipments

Specifications

Dimensions - in millimeters

	Length	Width	Height
External	1200	800	805
Internal	1120	720	660
Folded	1200	800	298

Nominal Capacity and Weight

Maximum capacity	565 ltrs 0.57 m ³
Maximum load weight	500 kgs
Tare Weight	45.2 kgs

Maximum load is 500 kgs for Container, 250 kgs on the Shelf

The optional lid weighs 7.3 kgs and the shelf 10 kgs.

Configuration and Stacking

Stacked layers in transit when open	6
-------------------------------------	---

Temperature Range

Minimum / Maximum	-20 °C / 40 °C
-------------------	----------------

Notes

Materials

High Density Polyethylene (HDPE) 100% Recyclable

Handling

Suitable to rack in either direction (1200 mm or 800 mm) using standard racking systems

Ensure the DRICON is fully supported by the racking system

Ensure that all doors and side panels are secured in their closed position.

Options and Accessories

Lid (CHEP Code 4141), Shelf (CHEP Code 4142)

CHEP Code

04140 - Dricon