

Overview

A reusable highly durable steel folding Intermediate bag-in-box Bulk Container for the packaging of non-hazardous liquid products.



Features and Benefits

Highly durable and suitable for multiple use.
 Easy to operate – Single operator can erect and fold down in 30 seconds.
 Folds down flat & packs 5 into 1 pallet space for efficient storage and transportation when empty.
 Stacks up to 5 units high when full.
 Spring-loaded baseboard ensures maximum discharge of product.
 Full height sight glass gives visual indication of contents.
 Component parts made from materials easy to replace and repair.
 Manufactured from fully recyclable materials making the product good for the environment.
 4 way pallet entry Galvanised mild steel, 30mm Galvanised steel frame, 0.9mm colour coated steel sheet.

Specifications

Dimensions - in millimeters			
	Length	Width	Height
External	1200	1000	1150
Folded	1200	1000	450

Nominal Capacity and Weight		
Maximum capacity		1000 ltrs
Maximum load weight		10000 kgs
Tare Weight		165 kgs

Configuration and Stacking		
Stacked layers in transit when open		5
Return ratio		5 : 1

Temperature Range	
Minimum / Maximum	-18 °C / 60 °C

Notes

Materials
 Frame: Silver Galvanised mild steel
 Panels: White 0.9mm colour coated steel sheet

Recommended Use / Applications

- Dairy
- Fruit
- Liquid Sugar
- Confectionery
- Beverages
- Food Oils
- Fragrances & Flavours
- Toiletries
- Cosmetics
- Detergent
- Adhesives
- Petrochemicals & Agrochemicals
- Paints
- Pharmaceuticals