

Euro Pallet

P1208B (Code 76-1120) plastic

1,200 x 800mm

Description

Reusable, heavy-duty plastic pallet with an anti-slip surface for the loading, displaying and distributing of raw materials and finished goods. It is pooled and serviced through CHEP's network of service centres, improving hygiene and efficiency across the supply chain and promoting a more sustainable use of natural resources.



Features and benefits

Designed to offer the highest hygiene standard

- + Water-resistant for easier cleaning and washing
- + Higher hygiene standards thanks to a non-porous surface that resists acids, fats and odours
- + Smooth surfaces and the absence of dead pockets mean no moisture, dust or liquid build-up. The risk of cross-contamination is reduced, making this the ideal pallet for hygienic areas and clean rooms.

Ideal for inbound logistics


- + Surface designed to prevent slippage, even when wet, for the safe transportation of raw materials to the manufacturer and finished goods along the supply chain
- + Maximises top deck space to allow full use of the pallet, reducing transport costs

Environmentally friendly

- + CHEP's pooling network reduces packaging waste and the overall impact on the environment

Warning: Please DO NOT rack across pallet width (80cm span) unless the three pallet skids are adequately supported. Avoid direct contact with the following substances: benzene and chlorine-based compounds, oleum, nitric acid, bromic acid and methyl bromide. Preliminary testing is recommended on each automated or gravity pallet handling system due to the bespoke nature of each technical set up. CHEP does not recommend the use of this pallet in direct contact with unpacked foodstuffs.

Specifications



DIMENSIONS AND TOLERANCES (mm)						
Detail	A	B	C	D	E	F
Nominal	1200	160	225	315	800	100
Minimum	1195	158	222	312	795	98
Maximum	1205	162	228	318	805	102

Materials and compliance

Made of strong, virgin HDPE with integrated steel reinforcements. Product is made from contamination-free materials (DIN 10503 and EHEDG) and/or components comply with ISO 8611-1991, JISz 0606 and ASTM D1185-94 standards.

Handling



Average weight



Stacking




Maximum loading capacity (dynamic)



Access



Do not use glue or staples



Temperature range

Robust integral construction

- + Optimised strength for the safe handling of heavy loads
- + No nails, sharp edges or splinters and therefore no risk of loose components. Improves conditions for load integrity across the supply chain.
- + Single-piece injection moulding with strong structural integrity makes repairs virtually unnecessary

Equipment compatibility

- + Fully compatible with crates and trays, providing a total plastic system
- + Can be used with all standard handling equipment
- + Four-way entry for easy access from multiple sides

Consistent quality

- + Dimensional accuracy makes it suitable for automated production, packaging and warehousing processes, minimising product damage and reducing downtime
- + Every pallet is carefully inspected and serviced to deliver improved conditions for health and safety

Colour coded blue

- + The distinctive CHEP blue colour ensures that our pallets can be easily identified

Important: CHEP pallets and containers always remain the property of CHEP and can never be legally bought or sold. CHEP reserves the right to change any of the above information without prior notice. To find out more, please visit www.chep.com