

**Overview**

CHEP's foldable container solutions are used by the automotive industries in Europe, the Americas, and Asia Pacific for both domestic and cross border supply chains.

The Foldable Large Container (FLC) builds on the proven performance of existing bulk containers. It is specifically designed to reduce the cost of relocating empty containers while providing maximum product protection and load stability.

The range of containers includes different heights to meet regional requirements and is accepted by the majority of automotive manufacturers and suppliers. The foldable pallet container has two access doors and four-way entry base.



**Features and Benefits**

**Features**

Fully foldable to maximise transport and storage space  
Industry standard design is light, sturdy and meets European regulations

**Benefits**

Fully recyclable materials minimise the impact on the environment  
Consistent specifications are suitable for automated production and line-side racking

**Specifications**

**Dimensions - in millimeters**

|          | Length | Width | Height |
|----------|--------|-------|--------|
| External | 1200   | 1000  | 975    |
| Internal | 1140   | 940   | 790    |
| Folded   | 1200   | 1000  | 295    |

**Nominal Capacity and Weight**

|                     |          |
|---------------------|----------|
| Maximum capacity    | 847 ltrs |
| Maximum load weight | 750 kgs  |
| Tare Weight         | 51 kgs   |

If inter-stacked with FLC 121097 – Classic, only fill with 500 kgs.

**Configuration and Stacking**

|  |    |
|--|----|
| Stacked layers in transit when open    | 3  |
| Stacked layers in transit when folded  | 10 |
| Stacked layers for storage when open   | 5  |
| Stacked layers for storage when folded | 20 |

**Temperature Range**

|                   |                |
|-------------------|----------------|
| Minimum / Maximum | -20 °C / 40 °C |
|-------------------|----------------|

**Notes**

**Materials**

**Base:** Polypropylene  
**Access doors:** Polypropylene  
**Sidewalls:** Polypropylene  
**Access Door Hinges:** - High Density Polyethylene  
**Sidewalls Clips:** Polyoxymethylene  
**Label Holders:** High Density Polyethylene

**Handling**

Where layer pads, durable trays, etc. are to be automatically loaded into the FLC, they should be a maximum size of 1102 x 900 mm to ensure unrestricted entry

FLCs should be lifted by fork lift truck through the pallet base windows. The forks should reach completely into the pallet base and enter the FLC squarely

FLCs should not be pulled or pushed along the ground

The dust cover should be kept with the FLC at all times

Do not use pallet jack through long sides entries to avoid skids damages.

When opening doors, push inwards and then lift.

**Recommended Use / Applications**

Automotive components, eg. Catalysts, Harnesses, Mudguards, Pedals, Radiator grilles