

Overview

CHEP's foldable container solutions are used by the automotive industries in Europe, the Americas, and Asia Pacific for both domestic and cross border supply chains.

The Foldable Large Container (FLC) builds on the proven performance of existing bulk containers. It is specifically designed to reduce the cost of relocating empty containers while providing maximum product protection and load stability.

The range of containers includes different heights to meet regional requirements and is accepted by the majority of automotive manufacturers and suppliers.



Features and Benefits

- Ensure superior product protection with robust design features including ergonomic latches & handles, wear & damage resistant material and modular construction
- Increases transport and storage space efficiency – containers are stackable when full or folded
- Ability to access bulk parts line side through the use of the side access doors
- Streamline line side processes with single person operation and the elimination of strapping and wrapping material
- Improve handling flexibility and product security with four-way forklift access
- Reduce time and effort for opening/closing access doors and collapsing containers with large, spring-loaded ergonomic latches
- Eliminate packaging waste and the associated time and cost with fully recyclable materials
- Reduces costs along the entire supply chain using a single container from Tier Supplier to line side

Specifications

Dimensions - in millimeters

	Length	Width	Height
External	1200	1000	975
Internal	1120	920	792
Folded	1200	1000	405

Nominal Capacity and Weight

Maximum capacity	816 ltrs
Maximum load weight	500 kgs
Tare Weight	62 kgs

Configuration and Stacking

Stacked layers in transit when open	2
Stacked layers in transit when folded	5
Stacked layers for storage when open	5
Stacked layers for storage when folded	12

Notes

Materials

Base, Access doors, Sidewalls, Door Hinges: HDPE
 Access Door Clips, Sidewalls Clips, Label Holders: Acetal

Handling

FLCs should be lifted by fork lift truck through the pallet base windows. The forks should reach completely into the pallet base and enter the FLC squarely
 FLCs should not be pulled or pushed along the ground
 The dust cover should be kept with the FLC at all times

Recommended Use / Applications

Catalysts, Harnesses, Mudguards, Pedals, Radiator grilles

Options and Accessories

CHEP can design the partition to match customer packing requirement if needed